

RELOOP RP7000 MK2 ?????



040277_reloop_rp7000_mkii_01_opt.jpg





Reloop RP-7000 MK2 ????? ? ???? ??? ?? ?????? ? ? ????????????, slipmat, LED ??????
 ?????, ?????, ????? RCA ? ???? , ????? USB, ????? ?????????.

?????????: ??? ?????????????? ??????

???? ?????

?????? ????? ?? ??? 629,99 €

???? ?????? 555,00 €

???????? ???? 107,42 €



?????? ? ? ?

????????????RELOOP

????????

Reloop RP-7000 MK2 ????? ? ???? ???? ???? ???? ???? ???? ???? ???? ???? slipmat, LED ?????? ???? ???? ???? RCA ? ???? ???? USB, ????? ???? ????.

?? RP-7000 MK2 ????? ?????????????????? ??? ????????, ?????????? ??? ?????????? ?????? ??? ??? ?????? ??? ?????????? ?????????? ??? ?????????? ?????????????? ??????????, ?????????? ?????? ??? booths ??? clubs, ??? ?????????? ?? ?????? ?????? ??? ?????????????? ??? ?????????????.

? ????????? ???? RP-7000 MK2 ?????? ????????? S ?? ?????????? ??????? ??? ?????????? anti-skating, ??????????? ?????????? ???????????
 ????? ???? ?????????????? ??????. ? ????????????????? LED ?????????? ??? ?????? ?????????? ????? ?????????? ??? ??? ?????? ??????? ??? ?????????? ??? ???
 ??????????? ??????? ????????? Start/Stop ?????? ?????????????? ??? ?? ?????????????????? ????? ??? ?????????? ??? ??? ??????????? ?????????????? ??? ??????
 ?? pitch ?????? ??????? ?????????????? ?? ?????? ??? ??????? ??? +/-8% ??? ??????? ?? ??????? ??? ?????????????? +/-50% (ultra pitch). ? ?????? ???
 ??????? ?????? ?????????????? ?????? ?????????????????? ?????????????? ?????? ?????????? ?????????? ??????????

?????? ?????????????????

?????:

- ?????: direct-drive turntable
- Drive: quartz driven upper-torque direct drive
- Motor: 16-pole, 3-phase, brushless motor
- Turntable speeds: 3 speeds, manual (33 1/3, 45, 78 RPM)
- Starting torque: 2.8 – 4.5 kg/cm (adjustable)
- Adjustable stop time (0.2 - 6 sec.)
- Start-up time / change to RPM: <0.2 sec
- Wow and flutter: 0.01% WRMS*
- S/N ratio: > 55dB (DIN-B)
- Brake system: electronic brake
- Record weight: recommended 800g

?????:

- ?????: die cast aluminium
- ?????????: 332 mm
- ?????: approx. 1.5 kg
- Tone arm:
- Type: universal, static balanced, S-shaped
- Effective length: 230 mm
- Overhang: 15 mm
- Tracking error range: < 3°
- Offset Angle: 22°
- Stylus Pressure: 0 - 4 g
- VTA setting range: 0-6 mm
- Useable weight of pick-ups: 3.5~8.5 g (incl. headshell 13~18 g)
- Anti-skating range: 0 – 3 g
- Effective tone arm mass: 12.8 g (incl. Reloop Headshell ~10 g)

?????????:

- 1x Phono/Line Out (gold-plated), 1x GND earth connection

?????:

- ?????????: AC 115/230 V, 60/50 Hz (EU/US), AC 100 V, 50/60 Hz (JP)
- ?????????: 13 W
- ?????????: 458 x 144.6 x 354 mm
- ?????: approx. 11.7 kg